

E-WASH 30

Multi-Surface Non-Ionic Building Wash

DESCRIPTION:

E-WASH 30 is a multi-surface non-ionic building wash for safe outdoor use. Provided as a concentrate, **E-WASH 30** is versatile enough for general cleaning of lightly soiled surfaces (when diluted) or as a heavy-duty degreaser concentrate to address greasy and oily soiled surfaces. It is designed to remove grease, oil, dirt, wax, ink, salts, residues and heavy soils from building surfaces, walls, floors, parking areas, outdoor patios, and other hard surfaces.

FEATURES:

- ✓ Low Cost
- ✓ Non-Toxic & Odorless
- ✓ Non-Corrosive
- ✓ Utilizes ingredients from the U.S. EPA's Safer Choice Program
- ✓ Non-Flammable
- ✓ Biodegradable
- ✓ Water Soluble
- ✓ Easy to Use

APPLICATION:

1. Dilution

For light or general cleaning, dilute one part **E-WASH 30** with 5-10 parts water. For heavier soil and degreasing, dilute one part **E-WASH 30** with 1-3 parts water. If necessary, **E-WASH 30** can be used undiluted for more difficult areas.



2. Application

E-WASH 30 may be applied by low-pressure spray, brush, sponge, or roller.

a. Minimum temperature is 40°F. Air, surface, and product temperatures must be above minimum and rising. Extend product dwell times when working at cooler temperatures. Additionally, using warm/hot water for dilution may reduce dwell times and improve overall effectiveness.

b. Application: Pre-dampen porous surfaces with clean water. Apply **E-WASH 30** lightly at desired dilution to surfaces intended for general cleaning. On heavily saturate greasy, oily, or heavily soiled areas, allow material to stand for up to 20 minutes, based on testing. Mock-ups and test areas are recommended to determine appropriate dilution and dwell times, and to ensure desired results are achieved.

For heavily soiled, oily, or greasy spots, work in with a stiff nylon bristle brush or broom and then allow to stand. After dwell time, rinse the material with clean water. Rinse thoroughly until all residue and foam have been removed. Some heavily encrusted areas may require a second application. Repeat as needed.

CAUTION: Some municipalities and other authorities may require the collection and proper disposal of all water and cleaners used for washing of building surfaces. Consult local regulations before use. Many stains, residues, and oily or greasy materials may require the collection of all rinse water. Dispose in accordance with federal, state, and local regulations.

3. Storage & Handling

Keep from freezing. After use, store remaining material in original tightly closed containers.

Avoid eye and prolonged skin contact. For complete safety and handling information, refer to Safety Data Sheet.

FOR COMMERCIAL AND INDUSTRIAL USE ONLY.



Washing a multi-color Aquathane UA210 terra cotta glaze coating with E-Wash 30 refreshes the appearance without damaging the coating.

 *Edison Coatings, Inc.*

Revised: 07/2021

3 Northwest Drive, Plainville, CT 06062

Phone: (860) 747-2220 or (800) 341-6621

E-mail: chad@edisoncoatings.com

Fax: (860) 747-2280 or (866) 658-1189

Internet: www.edisoncoatings.com

Edison Coatings products are for commercial use only. In case of defect in manufacture or packaging, materials will be replaced at no cost. No other warranty, except for such replacement, express or implied, is in effect. Any implied warranty of merchantability or fitness for a particular purpose is expressly disclaimed. Although information and advice supplied in this publication are believed to be reliable, they do not represent performance specifications and no obligation or liability is assumed for advice given or results obtained. Product formulations and performance characteristics are subject to change without notice. Other conditions and limitations may be imposed at time of sale.