# Safety Data Sheet

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### **Product Identification**

Product Name: System 90-W, 90-W Color, and 90-WL

Product Use: Sealer/Stain

# **Company Identification**

Edison Coatings, Inc. 3 Northwest Drive Plainville, CT 06062

**Edison Coatings Tech Info Phone:** 1-860-747-2220 **Emergency Phone:** 1-800-535-5053

# 2. HAZARDS IDENTIFICATION

# **Hazard Classification (GHS)**

Flammable Liquids......Category 4

Physical Hazards Not Classified

**Health Hazards** Sensitization, skin

**OSHA Defined Hazards** Not Classified

**Label Elements Hazard Pictograms** 



Signal Word: WARNING

#### Hazards

Combustible Liquid.

May cause skin irritation.

# **Precautionary Statements**

# **Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources Wash thoroughly after handling.

Wear protective gloves/clothing/eye protection/face protection.

# Response

IF SWALLOWED: Do not induce vomiting. If conscious, have victim drink plenty of water and call a physician immediately.

IF ON SKIN: Wash with soap and water. If skin irritation occurs: Get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

# **Storage**

Store in dry, cool environment.

# **Disposal**

Dispose of contents in accordance with local regulations.

# **Other Hazards**

No data available

# 3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight%	Chemical Name
Alkyl Phenol Ethoxylate Various	<0.1%	Various
Texanol 25265-77-4	<0.1%	Texanol
Ammonium Hydroxide 1336-21-6	<0.1%	Ammonium Hydroxide
Sodium Hydroxide 1310-73-2	<0.1%	Sodium Hydroxide
Methanol 67-56-1	<0.1%	Methyl Alcohol

#### 4. First Aid Measures

#### **Eye Contact:**

Flush eyes with plenty of water for 15 min. while holding eyelids open. Get medical attention.

# **Skin Contact:**

Wash affected areas with cool water.

#### **Ingestion:**

May be harmful if swallowed. Consult a physician.

#### **Inhalation:**

Remove victim to fresh air.

# **Medical Conditions Aggravated by Exposure:**

Pre-existing skin, eye, and lung disorders may be aggravated by this product.

# 5. FIRE FIGHTING MEASURES

# **Extinguishing Media:**

Foam, carbon dioxide, dry chemical, water fog

# Unusual fire and explosion hazards:

None

# **Fire Fighting Procedures:**

Do not enter enclosed spaces without full bunker gear, including positive pressure NIOSH approved self-contained breathing apparatus. Cool fire with water.

# 6. ACCIDENTAL RELEASE MEASURES

# Action to be taken if material is released or spilled:

If the material is spilled, remove with an inert absorbent.

# 7. HANDLING AND STORAGE

# Precautions to be taken in handling and storage:

Normal temperatures do not affect the material. Avoid breakage of packaged material or spills of bulk material. Avoid opening drums in unventilated areas to avoid concentrated ammonia vapors.

# 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

#### **Personal Protective Equipment**

# **Eye and Face Protection:**

Safety goggles.

#### **Skin Protection:**

Industrial work clothes should be worn. Waterproof gloves are recommended for direct contact.

#### **Other Personal Protection Data:**

Eye wash fountains and safety showers should be available for emergency use. No other special requirements are necessary.

# **Respiratory Protection:**

If spray mists are generated, wear NIOSH approved particulate respirator.

#### **Ventilation:**

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

# **Exposure Guidelines**

There is no data available on either OSHA Permissible Exposure Limits (PEL's) or ACGIH Threshold Limit Value (TLV's) for components of product.

# 9. PHYSICAL PROPERTIES

Odor: Slight Ammonia odor

Physical State: Liquid

pH: Not Determined Vapor Pressure (mmHg): >760 at 20°C Vapor Density (Air=1): Lighter than air

Boiling Point: 212°F Solubility in Water: Miscible

Coefficient of water/oil distribution:

Not Determined

Density (grams per milliliter):

Evaporation Rate (Ether=1):

Flash Point (Fahrenheit):

Flash Point (Celsius):

68.3

Lower Explosive Limit (%):

Upper Explosive Limit (%):

Autoignition temperature:

Not Determined

Not Determined

# 10. STABILITY AND REACTIVITY

Stability: All components are stable.

Conditions to Avoid: Sub-freezing temperatures
Incompatibility: Strong oxidizing agents

Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Normal decomposition products include

carbon dioxide, carbon monoxide, and

oxides of nitrogen.

Sensitivity to static discharge: Not determined.

# 11. TOXICOLOGICAL INFORMATION

# **Toxicity**

2-butoxyethanol is toxic by ingestion.

LD50, Oral-rat: 0.5 – 3.0 g/kg. LC50, inhalation-rat: 450 ppm/4H LD50, skin-rabbit: 0.4 g/kg

Although the concentration in this product is low, the high vapor pressure of 2-butoxyethanol makes it possible to exceed the TLV or PEL in the drum head space of confined areas.

# **Mutagens/Teratogens/Carcinogens:**

This product is not listed as a carcinogen by NTP, OSHA, or IARC. No constituents of this product are listed as carcinogens by NTP, OSHA, or IARC.

# 12. ECOLOGICAL DATA

No information on ecology is available.

# 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state, and federal regulations. This product is not a hazardous waste under RCRA Regulations (40 CFR 261), but may be regulated by other jurisdictions.

# 14. TRANSPORTATION INFORMATION

#### **US DOT & Canada TDG Surface**

Valuation.....: Not regulated for transport

approaching 0 °C (32 °F) or below.

This material does not sustain combustion.

Transport by sea IMDG-Code

Valuation....: Not regulated for transport

Air transport ICAO-TI/IATA-DGR

Valuation.....: Not regulated for transport

# 15. REGULATORY INFORMATION

#### **TSCA**

All components of this material are included on the Toxic Substances Control Act Inventory of Chemical Substances.

SARA Title III 311/312: Immediate acute hazard, fire hazard

# STATE LISTED COMPONENTS

2-Butoxyethanol	111-76-2	CA, FL, IL, LA, MA, ME, MN, NJ,
		PA, RI
Diethylene Glycol Monobutyl	112-34-5	CA, FL, IL, LA, MA, ME, MN, NJ,
Ether		PA, RI

# 16. OTHER INFORMATION

Effective Date: 22/Jan/2014 Revision Date: 14/Dec/2017